

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-085924

(43)Date of publication of application : 07.04.1998

(51)Int.Cl.

B22D 19/08
F16J 1/01
// F02F 3/00

(21)Application number : 08-246635

(71)Applicant : YANMAR DIESEL ENGINE CO LTD

(22)Date of filing : 18.09.1996


(72)Inventor : SHIROO KAZUHIKO
UENOSONO KINSAEMON

(54) METHOD FOR CASTING CYLINDER PISTON FOR DIESEL ENGINE

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent the occurrence of a shrinkage cavity caused by oriented solidification due to rapid cooling effect of a cooling metallic mold.

SOLUTION: The whole surface of inner side from the ridge line of outer peripheral surface at the top part of combustion surface of a piston is formed by a top part cooling metallic mold 3, the whole surface of side surface at the lower side from the ridge line at the top part of the piston is formed by a side surface cooling metallic mold 4 and the inner surface of a piston pin hole or the side end surface of a skirt part is formed by a piston pin cooling metallic mold 5 respectively. Each thickness of the cooling metallic molds 3, 4, 5, is regulated to 1/2-2 times of that of each thick part of a cylinder piston to be cast to unnecessitate feeder.



BEST AVAILABLE COPY